



PARALLEL TIP TRIMMING

The KBS Tour, Tour 90 and C-Taper shafts can be purchased in taper tip (.355) and parallel tip (.370). Listed below is the tip trimming instructions for the parallel tip shafts. This allows the club maker to achieve different flex and performance.

KBS TOUR [®] FST				
Step 1. Select your shaft and desired frequency				
	Softest ←		→ Stiffest	
Tour R Flex, 120g	4.0 Freq	4.5 Freq	5.0 Freq	5.5 Freq
Tour S Flex, 130g	5.0 Freq	5.5 Freq	6.0 Freq	6.5 Freq
Tour X Flex, 133g	6.0 Freq	6.5 Freq	7.0 Freq	7.5 Freq
Step 2. Tip trim shaft the amount below freq				
1-iron	0"	1 14/16"	1 14/16"	2 14/16"
2-iron	7/16"	1 7/16"	2 7/16"	3 7/16"
3-iron	1"	2"	3"	4"
4-iron	1 9/16"	2 9/16"	3 9/16"	4 9/16"
5-iron	2 2/16"	3 2/16"	4 2/16"	5 2/16"
6-iron	2 11/16"	3 11/16"	4 11/16"	5 11/16"
7-iron	3 4/16"	4 4/16"	5 4/16"	6 4/16"
8-iron	3 13/16"	4 13/16"	5 13/16"	6 13/16"
9-iron	4 6/16"	5 6/16"	6 6/16"	7 6/16"
PW	4 15/16"	5 15/16"	6 15/16"	7 15/16"
PERFORMANCE CHART				
Flex	Achievable Range			
Regular	4.0 fm - 5.5 fm			
Stiff	5.0 fm - 6.5 fm			
X-Stiff	6.0 fm - 7.5 fm			

KBS TOUR 90 [®] FST				
Step 1. Select your shaft and desired frequency				
	Softest ←		→ Stiffest	
Tour 90 R Flex, 101g	3.0 Freq	3.5 Freq	4.0 Freq	
Tour 90 S Flex, 102g	4.0 Freq	4.5 Freq	5.0 Freq	
Step 2. Tip trim shaft the amount below freq				
4-iron	0"	1.5"	3.0"	
5-iron	0.5"	2.0"	3.5"	
6-iron	1.0"	2.5"	4.0"	
7-iron	1.5"	3.0"	4.5"	
8-iron	2.0"	3.5"	5.0"	
9-iron	2.5"	4.0"	5.5"	
PW	2.5"	4.0"	5.5"	
PERFORMANCE CHART				
Flex	Achievable Range			
Regular	3.0 fm - 4.0 fm			
Stiff	4.0 fm - 5.0 fm			



Step 1. Select your shaft and desired frequency

	Softest ←→ Stiffest			
C-Taper R Flex, 125g	3.5 Freq	4.0 Freq	4.5 Freq	5.0 Freq
C-Taper S Flex, 135g	4.5 Freq	5.0 Freq	5.5 Freq	6.0 Freq
C-Taper X Flex, 140g	5.5 Freq	6.0 Freq	6.5 Freq	7.0 Freq

Step 2. Tip trim shaft the amount below freq

1-iron	3/16"	1 3/16"	2 3/16"	3 3/16"
2-iron	12/16"	1 12/16"	2 12/16"	3 12/16"
3-iron	1 5/16"	2 5/16"	3 5/16"	4 5/16"
4-iron	1 14/16"	2 14/16"	3 14/16"	4 14/16"
5-iron	2 7/16"	3 7/16"	4 7/16"	5 7/16"
6-iron	3"	4"	5"	6"
7-iron	3 9/16"	4 9/16"	5 9/16"	6 9/16"
8-iron	4 2/ 16"	5 2/ 16"	6 2/ 16"	7 2/ 16"
9-iron	4 11/16"	5 11/16"	6 11/16"	7 11/16"
PW	5 4/ 16"	6 4/ 16"	7 4/ 16"	8 4/ 16"

PERFORMANCE CHART

Flex	Achievable Range
Regular	3.5 fm - 5.0 fm
Stiff	4.5 fm - 6.0 fm
X-Stiff	5.5 fm - 7.0 fm